

ESTIMATION OF FLOW FOR UNGAUGED WATERSHEDS IN PRANHITA OF GODAVARI RIVER BASIN IN INDIA USING SWAT

Shuvra Sangeeta
Jacob CES (I) Pvt. Ltd., shuvra.san@gmail.com.

Debajit Basu Ray
Jacob CES (I) Pvt. Ltd.

Introduction

- The current study focuses on developing a model in SWAT that uses measured spatially and temporally varying inputs. It demonstrates that the comprehensiveness in the model's interrelationship after calibration at gauged locations, combined with incorporating the spatio-temporal heterogeneity of climate and landscape properties in a basin, can be used to predict flow at watershed scale ungauged locations.
- The finding of the study shows that, given appropriate spatial and temporal input, SWAT can provide a satisfactory simulation of the water budget at ungauged sites, when calibrated at a basin scale.

Presentation Outline

Study Area : Pranhita River Basin

Soil and Water Assessment Tool (SWAT) Model set up

- ❖ DEM
- ❖ Soil
- ❖ Landuse
- ❖ Weather

Calibration and Validation data

Naturalisation : Approach

Water Balance

Results and discussion

Conclusion

Further prospects of the study


Acknowledgement

Study area

Pranhita sub-basin belongs to Godavari basin, comprising of rivers Pranhita, Penganga and Bhima draining an area of 209,079 km².

Rainfall :
Annual rainfall variation is
1000mm - 1900mm

Flow :
Average 1063 cumec
Minimum 1.1 cumec
(June 2005)
Maximum 38914 cumec



Study area


Nainganga rises at an altitude of 640m in the Satpura range in Seoni district of Madhya Pradesh. Winding through the spurs of hills from west to east for a short distance, it flows south and west through Bhandara, Rat and Pauni area. The catchment area of the river upto its confluence with Wardha is 51,000 km².



Study area

Iha is the right bank tributary of Pranhita with its origin at Dahawadhna peak at 777 m in the Satpura range in Betul district of Madhya Pradesh. After traversing 528 km, it joins Wardha river at Seoni, draining a catchment of 48,000 km².

The combined water of Wardha and Pranhita flows joins Godavari near Kaleshwaram in Andhra Pradesh near the Maharashtra border.




Study area

major tributary of Wardha river Enganga which originates from Ajantha hills at an altitude of El 686m in Nandgaon district in Madhya Pradesh. It flows along the state border between Maharashtra and Andhra Pradesh along south-east and turns along U shape twice to converge into Wardha river near Wadhna village. The total length of the river is 676 km and total catchment area upstreams confluence with Wardha is 3,898 km².



Study area

Tekra : Flow (cms)



Soil Water Assessment Tool (SWAT)

SWAT is a river basin scale Long-term, continuous watershed simulation model (Arnold et al,1998)


Assesses impacts of climate and land management on yields of water, sediment, and agricultural chemicals

Physically based, including hydrology, soil temperature, plant growth, nutrients, pesticides and land management

It is a public domain model actively supported by the USDA Agricultural Research Service at the Grassland, Soil and Water Research Laboratory in Temple, Texas, USA.

The SWAT system (ArcSWAT/MWSWAT) is embedded within geographic information system (GIS), and can integrate various spatial environmental data, including soil, land cover, climate, and topographic features.

Sub basins and HRUs (268)



SWAT model setup

M

Topographic Elevation dataset (DEMs) at 90m resolution was obtained from the NASA Shuttle Radar Topographic Mission (SRTM) website.

basin has medium topographic relief

Elevation in the basin 1086m-95m. Mean Elevation is 360m a.m.s.l

Average slope of the sub-basin is 1.6%.

L

soil map by Food and Agriculture Organisation of the United Nations (1995) with a spatial resolution of 10km as per AISLUS Classification, was used.


The soil of Pranhita sub-basin is predominantly clay with clay loamy soil interspersed throughout the basin.

Swat model setup

LAND USE

The Landuse map is from USGS Global Land Cover Characterisation (GLCC) database (April 1992-March 1993)
<http://edcns17.cr.usgs.gov/glcc/glcc.html>.

% agriculture
% pasture
% forest .



Swat model setup

WEATHER



National Climate Centre (NCC) of Indian Meteorological Department (IMD) daily precipitation and temperature values at 0.5 and 1 degree interval respectively

Wind speed and solar radiation were simulated from the nearest climate station using the weather generator in SWAT.


Evapotranspiration was calculated within the model using Penman-Montieth Method (Montieth, 1965).

Swat model setup

daily
temp (°C)



Annual
Rainfall
(mm)



Calibration and validation Data

The daily and monthly streamflow observation data from CWC (Central Water Commission) maintained gauging stations viz. Ghugus (Wardha sub-basin), P G Bridge (Penganga) and Tekra (Pranhita) are used for calibration and validation.

Annual sub-basin level utilisation from National Water Development Agency (NWDA) sub-basin Reports of Godavari

Utilisation

There are four major Projects, 37 medium Projects and minor projects of 1028 M cu m utilization capacity existing in truncated Pranhita.

In the Penganga sub-basin, two major projects and seven medium Projects and several Minor schemes existing which indicates utilization of about 18%

In the Wardha sub-basin, Sixteen medium projects and several *Minor schemes of 202 M cu m* capacity shows utilization percent of 12%.

Overall, there is over 12% utilization in Pranhita basin based on information collected upto 1992-93.

Naturalisation : Approach


basin level Annual utilization collected from Reports. The utilization comprises of irrigation, water supply, return flows, evaporation loss.

aggregate into monthly utilization based on cropwater requirement.

Non-Monsoon utilization is added to Monsoon months in proportion to the rainfall received.

For gauging sites located inside the basin, the annual utilization is derived on pro-rata basis from design capacity of projects located in its catchment to the basin level design capacity.

Water Balance



Water Balance Ratios	
Streamflow/Precip	0.38
Baseflow/Total Flow	0.23
Surface Runoff/Total Flow	0.77
Perc/Precip	0.17
Deep Recharge/Precip	0.05
ET/Precipitation	0.54

Results and discussion

meter	Description	Unit	Default value	Calibrated value
	Soil Evaporation compensation factor	fraction	0.95	0.7
AWC	Available soil water capacity	mm mm ⁻¹	0.1-0.18	0.18-0.32
MN	Threshold water depth in shallow aquifer for return to occur	mm	0	100
RGE_DP	Deep aquifer percolation fraction	fraction	0.05	0.3

Results and discussion

	Catchment Area (km ²)		Period	Monthly		Annual		
	R ²	NSE		PBIAS	R ²	NSE		
Kra	108780	Calib	1971-72 to 1983-84	0.95	0.94	-10	0.92	0.83
Pranhita		Valid	1984-85 to 1993-94	0.97	0.95	-16	0.98	0.84
ugus	21429	Calib	1971-72 to 1983-84	0.92	0.91	-5	0.93	0.88
Wardha		Valid	1984-85 to 1993-94	0.9	0.87	-15	0.9	0.76
Gidge	18441	Calib	1971-72 to 1983-84	0.95	0.95	-7	0.94	0.93
Penganga		Valid	1984-85 to 1993-94	0.93	0.92	-9	0.96	0.95


Results and discussion

	Catchment Area (km2)	Average			Standard deviation	
		Observed	Naturalised	Simulated	Observed	Simulated
Asthi	50990	680	784	893	389	346
Bamni	46020	335	362	426	206	192
Bishnur	5000	20.1	20.2	29.8	16	18.6
Ghugus	21429	146	154	211	88.5	90.6
Hivra	10240	44.6	46	71.9	34	38.3
Kanhargaon	3515	16	20	24.1	14.3	19
Keolari	2970	33.8	34.3	44.9	21.2	20.5
Kumhari	8070	111.2	114.9	138.6	69.2	58
Marlegaon	7410	35.9	39.9	58.9	31.6	38.9
Nandgaon	4580	26.7	34.6	49.2	17.9	24
Pauni	35520	347	440.7	617.6	210	252.1
P G Bridge	18441	132.3	144.4	168.6	86.3	91.9
Rajegaon	5380	111.8	121.1	141.6	79.8	56.4
Rajoli	1900	21	25.3	30.1	12	16.1
Satrapur	11100	81.2	111.2	129.1	55.7	60.4
Sirpur	47500	370.3	415.5	476.4	230.8	199.6

Results and discussion


	Catchment Area (km ²)	Annual		PBIAS (%)	Monthly	
		R ²	NSE		R ²	NSE
Asthi	50990	0.97	0.92	-8.3	0.94	0.94
Bamni	46020	0.95	0.86	-16.8	0.93	0.9
Bishnur	5000	0.79	0.09	-44	0.71	0.3
Ghugus	21429	0.98	0.63	-37.4	0.81	0.62
Hivra	10240	0.89	0.15	-56	0.82	0.59
Kanhargaon	3515	0.97	0.94	-7	0.82	0.81
Keolari	2970	0.91	0.69	-24.5	0.9	0.85
Kumhari	8070	0.97	0.85	-15.7	0.92	0.91
Marlegaon	7410	0.99	0.57	-41	0.91	0.81
Nandgaon	4580	0.94	0.33	-38	0.94	0.71
Pauni	35520	0.97	0.54	-29.1	0.93	0.73
P G Bridge	18441	0.97	0.89	-16.7	0.94	0.88
Rajegaon	5380	0.71	0.62	-16.9	0.77	0.76
Rajoli	1900	0.93	0.72	-15	0.93	0.91
Satrapur	11100	0.85	0.71	-16.1	0.81	0.66
Sirpur	47500	0.98	0.9	-14.7	0.93	0.91

Result and discussion : Tekra - Calibration




	Catchment Area (km²)	Period	Monthly		Annual		
			R²	NSE	R²	NSE	PBIAS
Tekra	108780	Calib	0.95	0.94	0.92	0.88	-6

Result and discussion : Tekra - Validation




	Catchment Area (km²)	Period	Monthly		Annual			
			R²	NSE	R²	NSE	PBIAS	
Tekra	108780	Calib	1971-72 to 1982-83	0.95	0.94	0.92	0.88	-6

Result and discussion : Tekra - Calibration



	Catchment Area (km ²)		Period	Monthly		Annual		
	R ²	NSE		R ²	NSE	PBIAS		
Tekra	108780	Calib	1971-72 to 1982-83	0.95	0.94	0.92	0.83	-10

Result and discussion : Tekra - Validation





	Catchment Area (km ²)		Period	Monthly		Annual		
	R ²	NSE		R ²	NSE	PBIAS		
kra	108780	Calib	1971-72 to 1982-83	0.95	0.94	0.92	0.83	-10
		Valid	1983-84 to 1992-93	0.97	0.93	0.97	0.86	13

Validation Results

Result and discussion : Kanhargaon

CA -3515 sq km
Sub-basin -Penganga





	Catchment Area (km ²)	Period	Monthly		Annual		
			R ²	NSE	R ²	NSE	PBIAS
Bridge	18441	1971/72 to 1982/83	0.05	0.05	0.04	0.03	7

Result and discussion : Asthi

CA -50990 sq km

Sub-basin - Pranhita





	Catchment Area (km ²)	Period	Monthly		Annual			
			R ²	NSE	R ²	NSE	PBIAS	
Tekra	108780	Calib	1971-72 to 1982-83	0.95	0.94	0.92	0.83	-10

Result and discussion : Keolari

CA – 2970 sq km

Sub-basin - Wainganga



Catchment Area

(km²)

Period

Monthly

Annual

R²

NSE

R²



NSE

PBIAS

Result and discussion : Rajoli

CA – 1900 sq km

Sub-basin - Pranhita





	Catchment Area		Period	Monthly		Annual		
	(km ²)			R ²	NSE	R ²	NSE	PBIAS
T1	1887.82	6.41	1971-72 to 1982-83	0.85	0.84	0.82	0.82	-16

Some low Statistics

Result and discussion : Bishnur

CA – 5000 sq km



Sub-basin - Wardha



	Catchment Area (km ²)	Period	Monthly		Annual		
			R ²	NSE	R ²	NSE	PBIAS

Result and discussion : Nandgaon

- CA – 4580 sq km
- Sub-basin - Wardha





	Catchment Area (km ²)	Period	Monthly		Annual		
			R ²	NSE	R ²	NSE	PBIAS
ghus	21249	Calib	0.92	0.91	0.93	0.88	-5

Result and discussion

analysis of wetter than normal years and drier than normal years shows that the model gives better results in wetter years than drier years.

The monthly NSE's for TWYLD are 0.95 for the three wet years and 0.67 for the four drier years.

A comparison of the monthly observed and simulated streamflow for the wet year with highest peak and dry year with the lowest peak reveal that the model tended to overpredict streamflow during the monsoon period of the year.



Conclusion

The SWAT model developed in the study validates how well spatially distributed models are able to produce acceptable results using readily available, physically based input parameters in watersheds ranging from small to very large. Given further information about the watershed's physiographic characteristics, better simulation results would be obtained, especially on a monthly temporal scale.

The calibrated SWAT model is tested for streamflow. We used annual and monthly streamflow from 16 CWC monitoring gauges to test SWAT and found that SWAT can capture the amount and variability of annual streamflow acceptably well (R^2 values range between 0.72 and 0.99 and NSE ranges between 0.94 and 0.54).

Conclusion

The low statistics of Bishnur/Nandgaon may be attributed to :

- Lack of sufficient information about the utilization details from minor irrigation projects in the upper reaches of Wardha basin, in particular.
- Major change in Water utilization due to projects in Wardha post 1990 for which data is not available

Overall, the SWAT model can satisfactorily predict hydrologic budget for the ungauged basins in Pranhita with calibration at basin scale. The results further emphasize the importance and prospects of using accurate spatial input data for ungauged flow assessment using the physically based SWAT model .

The Simulation is being tested on utilization of time line 1972 to 1993 which is dynamic in nature.

Further prospects of the study

- | The study also highlights the prospect of simulation of effect of change in landuse on ungauged catchments and their combined effect on basin scale.
- | The effect of climate change on small ungauged basins

Disclaimer

- The views expressed by the authors in the presentation are purely individual and do not reflect the views of the organization in any way.

Acknowledgement

- We express gratitude to SWAT Research team to show interest in the findings of studies undertaken by us using SWAT model.
- Our thanks to Prof. Subhash Chander to initiate and encourage study in the application of SWAT model.

Reference

- Arnold, J. G., D. N. Moriasi, P. W. Gassman, K. C. Abbaspour, M. J. White, R. Srinivasan, C. Santhi, R. D. Harmel, A. van Griensven, M. W. Van Liew, N. Kannan, M. K. Jha. 2012 . SWAT Model use, Calibration and Validation. ASABE. 55(4) : 1491-1508.
- Lee T., R. Srinivasan, J. Moon, N. Omani. 2011. Estimation of Fresh Water Inflows to Bays from Gaged and ungauged Watersheds. ASABE. 27(6): 917-923
- Srinivasan, R., X. Zhang, J. Arnold. 2010. SWAT Ungauged : Hydrological Budget and Crop Yield Predictions in the Upper Mississippi River Basin. ASABE. 53(5): 1533-1546
- Water Balance Study of Penganga, NWDA, 1999)
- Water Balance Study of Wardha, NWDA,2001)
- Water Balance Study of Pranhita, NWDA,2001)

Thank You

