

SWAT+ application to simulate and evaluate water management actions impacts on model performance and streamflow regime

Alejandro Sánchez-Gómez, Aruca Pedrero-Redondo, Eugenio Molina-Navarro

SWAT Conference

October 2025
Fort Collins, Colorado (US)





Hydrological and Water management models

Hydrological models (SWAT, MIKE SHE, TOP Model, etc.).

- ✓ Focused on the simulation of hydro-environmental processes.
 - ✓ Evaluation of water resources availability under climate change).



 Common procedure → Coupling models (Hydrological models outputs used as inputs in Water management models)

agement actions.

Water manageme BASIN, WEAP, AC

Including the simulation of water management actions in hydrological models

ment actions.

√aluate scenarios (e.g.,





demand increase).

Most lack hydrological processes simulation (require hydrological inputs).

Water management simulation with SWAT+

Decision tables

Water allocation module



Example res_rel.dtl file 1						CONDITIONS					ALTERNATIVES			
					ACT	IONS	CONFIC	GUI	RATION	ACTI	ONS EX	ECUTI	ON	
name		conds	alts	acts										
ex_rel_	table	4	5	4										
var	obj	obj_:	num	lim_var	lim	op	lim_cons	st	alt1	alt2	alt3	alt4	alt5	
month	null	0		null	_		6.00000		>=	<	-	-	-	
month	null	0		null	_		8.00000		<=	-	>	-	-	
vol	res	0		pvol	*		1.00000		<	<	<	>	-	
vol	res	0		evol	*		0.95000		-	-	-	-	>	
act typ	obj	obj :	num	name		optio	on	CO	nst	const2	fp	outc	ome	
release	res	0		summer_ra	ate	rate		0.	10000	0.00000	null	y n	n n n	
release	res	0		winter_r	Lse	inflo	_frac	0.	15000	0.00000	null	n y	y n n	
release	res	0		full_rlse	9	days		5.	00000	0.00000	pvol	n n	n y n	
release	res	0		emerg rls	se	ab er	ner	0.	00000	0.00000	null	n n	n n y	

.DTL FILES IN SWAT+

Water management simulation with SWAT+

Decision tables

Water allocation module

Allow to configure water movements between SWAT+ objects (irrigation, water transfers, diversions)



These novelties

- regulated basins
- Enhance the capabilities and usefulness of the model
 → Simulation of water management scenarios

													1	
												1	1	1
ı	10	hru	341	irr_crt	15	sr	null	null	null	0	null	1	1	1
ı	11	hru	342	irr_crt	15	sr	null	null	null	0	null	1	1	1
ı	12	hru	343	irr_crt	15	sr	null	null	null	0	null	1	1	1
ı														

SOURCES

MINIMUN WATER AVAILABILITY

DEMAND OBJECTS


DEMAND CONDITIONS


ugh decision tables

The Tagus River basin (TRB)

International basin

 Most populated in the Iberian Peninsula (10 million inhabitants)





Upper Tagus River basin (UTRB)


41% of the TRB (34,000 km²)

Most populated part (7.5 million inhabitants)

Source of the Tagus Segura Water Transfer (TSWT, diverts 330 hm³/year)

The UTRB supplies most of the water demand in the TRB →

Priority region to assess water resources availability




OBJECTIVES

Objectives

- Improving the simulation of water management in the UTRB using SWAT+
- Design, simulate and compare management scenarios impact on

 i) model performance and
 ii) streamflow regime



PREVIOUS WORK: DEVELOPING A REALISTIC MODEL


REALISTIC SIMULATION
OF HYDROLOGICAL PROCESSES

IMPLEMENTING THE SIMULATION OF WATER MANAGEMENT

REALISTIC SIMULATION OF HYDROLOGICAL PROCESSES

Model calibration

Model calibration → Zonal calibration (geological regions) and in natural regime areas




Sánchez-Gómez, A., et al. (2025). Multi-spatial and multi-criteria calibration to guarantee a robust SWAT+ hydrological model in a large and heterogeneous catchment. CATENA, 261, 109508.


CATENA

Aggregation of streamflow (daily) of calibrated sub-catchments

Aggregation of reservoirs inflow (monthly)



IMPLEMENTING THE SIMULATION OF WATER MANAGEMENT



IMPROVING MANAGEMENT IMPLEMENTATION

IRRIGATION

WATER TRANSFERS


Water management implementation: Room for improvement

Irrigation

Simulated demand → 97% of the estimated

Simulated irrigation → 71% of the estimated demand

Simulated demand timing can be improved



Estimated demand

Simulated demand

Irrigation

Changes in irrigated HRUs

Irrigated HRUs were compared with different land-use datasets (CLC + SIOSE + Satellite image) →


Some of the HRUs that were poorly irrigated were actually not irrigated crops →

Converted to rainfed cereals

Changes in plant management and parameters

Days to mature parameter reduced (from 150 to 120 days) to favour a **quicker development of the plant** (corn)

Plant cycle was **brought forward** by 15 days







Irrigation

Changes in water allocation file:

Previous water allocation tables -> Closest channel was the only source

NAME	RULE	_TYP		SR	C_OBS	DMD_OE	SS CHA_DE	3							
channel_163_irri	g high	_right_fir	st_serve	1		4	У								
SRC_NUM OB_TYP	OB_N	UM JAN_MIN	FEB_MIN	MAR_M	IN APR_M	IN MAY_	MIN JUN_	MIN JUL_M	IN AUG_MI	N SEP_M	IN OCT	_MIN N	NOW_MIN	DEC_MI	1
1 cha	163	0.01	0.01	0.0	1 0.	01	0.01	0.01	0.01	0.01	0.0	1	0.01	0.01	0.01
NUMB OB_TYP (OB_NUM	WITHDR	AMOUNT	W_RT	TR_TYP	TREAT	RCV_OB	RCV_NUM	RCV_DTL	SRCS	SRC1	FRAC1	COMP1	SCRC2	FRAC2 COMP2
1 hru	3674	irr_crt	12	sr	null	null	null	0	null	1	1	1	n		
2 hru	3675	irr_crt	12	sr	null	null	null	0	null	1	1	1	n		
3 hru :	3676	irr_crt	12	sr	null	null	null	0	null	1	1	1	n		
4 hru	3677	irr_crt	12	sr	null	null	null	0	null	1	1	1	n		

Now -> Closest aquifers are used as secondary source that compensate if demand is not fully supplied

Irrigation amount slightly modified


NAME			TYP			C_OBS	DMD_O	BS CHA_DI	3								
chan	nel_146_irr	ig high	_right_fir	st_serv	e 2		4	У									
SRC_	NUM OB_TYP	OB_N	IUM JAN_MIN	FEB_MI	N MAR_M	IIN APR_N	IIN MAY	MIN JUN	MIN JUL_M	MIN AUG_MI	N SEP_	MIN OCT	_MIN N	NIM_VO	DEC_MI	N	
1	cha	163	$0.0\overline{1}$	0.01	0.0	0 $\frac{1}{0}$.	.01	0.01	0.01	0.01	0.01	0.0	1	0.01	0.01	0	.01
2	aqu	13	15	15	15	15)	15	15	15	15	15		15	15	1	5
NUMB	OB_TYP	OB_NUM	WITHDR	AMOUNT	W RT	TR_TYP	TREAT	RCV_OB	RCV_NUM	RCV_DTL	SRCS	SRC1	FRAC1	COMP1	SCRC2	FRAC2	COMP2
1	hru	3674	irr_crt	13	sr	null	null	null	0	null	2	1	1	У	2	0	У
2	hru	3675	irr_crt	13	sr	null	null	null	0	null	2	1	1	У	2	0	У
3	hru	3676	irr_crt	13	sr	null	null	null	0	null	2	1	1	У	2	0	У
4	hru	3677	irr_crt	13	sr	null	null	null	0	null	2	1	1	У	2	0	У

Irrigation improvement

Basin scale (average annual)

Variable	Mode	el	Improvement
Variable	Previous	New	(h m ³)
Observed demand (hm³)	421	421	-
Simulated demand (hm³)	409	421	12
Simulated demand (%)	97.1	100	-
Simulated withdrawal (hm³)	299	350	51
Observed demand met (%)	71.0	83.1	-

- ✓ Improved demand simulation
- ✓ Noticeable improvement in the amount supplied
- ✓ Seasonality better reproduced



Water management implementation: Room for improvement

Water transfers

- Simulated demand → 100% of the estimated
- Demand supplied → 90% of the demand (1,050 hm³/y)
- TSWT simulated at 80%
- Some transfers had a channel as source (small reservoirs not included in the model) →
 Poorly supplied

	Water transfer	Observed amount (hm³/year)	Simulated demand (hm³/year, % of observed)	Simulated water transfer (hm³/year)		nd
	TSWT	358.10	357.85 (100)	283.46	79.21	%)
	Atazar Canal	167.73	167.7 (100)	167.70	100.00	
Total U	Valmayor Canal	100.33	100.26 (100)	88.21	87.98	0
	Jarama Canal	88.82	88.82 (100)	86.08	96.91	
	Cazalegas irrigation Canal	78.80	78.82 (100)	77.64	98.50	
Туре	Picadas and AMSO canals	69.00	68.54 (99)	67.28	98.16	
WateWate	San Juan Canal	64.26	64.31 (100)	64.31	100.00	
• With	Santillana Canal	51.94	51.97 (100)	51.97	100.00	man .
	El Vellón and Guadalix canals	32.79	32.72 (100)	32.72	100.00	7
	El Villar Canal	30.02	30.02 (100)	30.02	100.00	
5	Almoguera Canal	30.00	30.06 (100)	29.93	99.55	and the
	Las Nieves Canal	28.38	28.44 (100)	14.55	51.15	
	Trillo nuclear plant	18.00	18.74 (104)	18.74	100.00	
,	La Jarosa Canal	14.79	14.78 (100)	5.86	39.67	³/year)
	Sorbe Canal	12.55	12.47 (99)	12.47	100.00	
<	Navacerrada Canal	10.00	10.01 (100)	3.99	39.88	
	La Aceña Canal	9.81	9.78 (100)	9.78	100.00	
	Navalmedio Canal	4.65	4.66 (100)	4.36	93.62	ment
	La Pinilla Canal	3.72	3.64 (98)	3.64	100.00	
	Aceca power plant	0.80	0.79 (99)	0.79	100.00	

Water transfers Small source reservoirs introduced Simulated Simulated demand Observed Las Nieves Demand water (hm³/year, Water transfer amount 0.22 hm³ transfer met (%) (hm3/year) % of (hm³/year) observed) Las Nieves 28.38 28.44 (100) 14.55 51.15 Canal 39.67 La Jarosa Canal 14.78 (100) 5.86 La Jarosa 14.79 7.15 hm³ Navacerrada 10.00 10.01 (100) 3.99 39.88/ Canal **New configuration for the TSWT** Navalmedio Navacerrada $0.51 \, hm^3$ 11.04 hm³ Simulated Simulated Observed demand water Demand (hm³/year, Water transfer amount met (%) transfer (hm³/year) % of (hm³/year) observed) 357.85 79.21 **TSWT** 283.46 358.10 **Entrepeñas** (100)802 hm³ Buendía (40%) Entrepeñas (60 %) New connections adapted in the water allocation file Buendía **Bolarque** La Bujeda 1651 hm³ 6.73 hm³ 31 hm³

Water transfers


Including water consumption fraction

Before → All water for human consumption (~600 hm³) returned to the rivers

Now → Only 70 % return, and 30 % is removed (180 hm³)

flo_con tables duplicated →

To configure the **70-30 proportion**



41.0°N Consumptive use Water transfer outside basin Water transfer within basin Withdrawal and Return 40.5°N Water movement ▲ Extraction ∇ Return Volume 40.0°N (hm³/year) **→** 20 **→** 50 **→** 100 **200 300**

Water allocation tables duplicated → Same source, but now 2 receiver objects (*consumptive* and *return*)

9 divert 1 wr_jarama_1_ret
9 divert 1 wr_jarama_1_cons

0.0 sr null null cha 155 null 1 3 1.0 n
0.0 sr null null cons 1 null 1 3 1.0 n

Water transfers improvement

Individual water transfers


	Observed demand	Simulated	Simulated t		hange	
Water tranfer			(% of obse		Tidlige	
	(hm³/year)	demand (%)	Previous model	New model	%	hm³/year
TSWT	357.9	99.5	79.2			
Valmayor canal	100.3	99.5	88.0			
Las Nieves canal	28.4	99.8	51.3			_
La Jarosa canal	14.8	99.5	39.6			
Navacerrada canal	10.0	99.7	39.9			

Out
Withdrawal-return
Between reservoirs

Basin scale


Model	Observed demand		Simulated transfer			
	(hm³/year)	demand (%)	(% of observed)	hm³/y		
Previous	1168.9	100	90.1	1053.5		
New	1106.9	100	97.5	1139.5		
		Improvement	7.4	86.0		


Basin outlet performance improvement





DESIGN AND SIMULATION OF WATER MANAGEMENT SCENARIOS


Management scenarios















Average streamflow at basin outlet:

Scenario	Basin discharge (hm³/y)	Change regarding natural regime (%)
1: Natural regime	2843	-
2: Only reservoirs	2776	-2
3: Reservoirs and irrigation	2488	(-12) Irrigation
4: Reservoirs and transfers inside the basin	2600	(-9) Consumptive use
5: Reservoirs and transfers outside the basin	2331	(-18) WT Outside (TSW
6: Reservoirs and all water transfers	2158	-24
7: Full management	1871	(-34)


Impact on streamflow regime

Average monthly streamflow: Natural regime vs. Scenarios and observed




Impact on streamflow regime

Variation of monthly streamflow: Scenarios and observed vs. Natural regime scenario



DESIGN AND SIMULATION OF WATER MANAGEMENT SCENARIOS




CONCLUSIONS

The implementation of management actions was improved compared to the previous model.

- Irrigation demand (+12 hm³/y) and water supply (+51 hm³), as their timing, were better simulated.
- Water transfers simulation was increased by 86 hm³ (7 % of total demand), enhancing the simulation of some key transfers such as the TSWT.
- Despite some room for improvement (further work), the **streamflow simulation** at the end of the catchment **was noticeably improved** (PBIAS reduced to satisfactory values).

Six water management scenarios were compared with a natural regime one.

- Water management impacted streamflow in a large extent, both in magnitude and seasonality. The impact of water transfers outside the basin was found the largest (-18 % of streamflow at the outlet compared to natural regime), followed by irrigation (-12 %) and water consumption (9 %).
- The impact on the seasonality clearly differs among scenarios.
- The **simulated impact is still lower than the observed** (bias in simulated streamflow + bias in simulated management).


















Water resources and their management


Water resources per capita → Halved in the last 50 years (FAO-Aquastat, 2021)




Generated from FAO-Aquastat (2021)

Severe water stress \rightarrow Affects 2/3 of the world population at least during one month per year (Mekonnen & Hoekstra, 2016)


 $Water\ stress = \frac{Water\ demand}{Renewable\ water\ resources}$






Sánchez-Gómez, A., et al. (2025). Using sensitivity analysis and soft calibration of geological regions to improve the representation of hydrological processes in a SWAT+ model. Hydrological Sciences Journal, 1-18. https://doi.org/10.1080/02626667.2024.2446268

Hard calibration





Initial parameterization: Crops distribution and management

Rainfed arable crops \rightarrow Different SWAT land use for each main province

Land use split into **dominant crops** → Different proportions (MAPA, 2020)


Cereals split to allow **different states** of the rotation **Wheat/Barley/Fallow**

Drovingo	Agricultural land use split								
Province •	Group 1	Group 2	Group 3	SUNF	FPEA				
Ávila	23%	22%	22%	32%	1%				
Madrid	22%	21%	21%	31%	5%				
Cuenca	26%	26%	26%	18%	4%				
Guadalajara	30%	29%	30%	1%	10%				
Toledo	I 31%	30%	31%	1%	7%				

Irrigated crops → Individual land use









Water management implementation

Irrigation implementation


- 97% of the estimated demand was simulated
- The seasonal pattern was reproduced
- 73% of the simulated demand was met → 299 hm³/year






Water management implementation

Water transfers implementation




Streamflow comparison: Water transfers vs. no water transfers



Water management implementation: Room for improvement

Reservoirs

- Satisfactory simulation of many, but room for improvement in others
- Improving reservoirs is work in progress
 - New reservoirs introduced
 - Edits in some decision tables



Water management implementation

How does implementing management actions affect the UTRB outlet?

Improved low flows and high flows simulation

NSE improved, but still very low R² slightly worse

PBIAS and RMSE → Error reduced by 50%

Still 40% of PBIAS

